

A-Core Container

Base station power supply current



Overview

What does a 42 volt power supply mean?

42V. It means that if the voltage drop is more than 6V, the ICT equipment will be protected. It can be seen that when the length more than 120m in the 4G system and the length more than 70m in the 5G system, the ICT equipment will be off because the low voltage protection of the power supply system.

What is a 3G base station converter?

In a 3G Base Station application, two converters are used to provide the +27V distribution bus voltage during normal conditions and power outages.

What voltage does a DSL power system supply?

The DSL power system may supply both higher voltage analog line drivers and amplifiers (typ. +/-12V) and several low voltage supplies required by the digital ASIC (+5V, +3.3V, +1.8V, +1.5V).

What is a multi-output power supply design?

Multiple output designs may also employ a complex regulation scheme which senses multiple outputs to control the feedback loop. Voice-over-Internet-Protocol (VoIP), Digital Subscriber Line (DSL), and Third-generation (3G) base stations all necessitate varying degrees of complexity in power supply design.

What is a low profile power supply?

Low profile power supply design usually includes printed circuit board (planar) power transformers and output inductors and surface mount input and output capacitors. Multiple output power supplies are often implemented with a multi-output flyback converter.

How much power does a PSU need?

This is when the PSU is no longer powering the PA, which is the main power

draw, but still needs to power other electronics. The current target for low-load efficiency is about 30 W. Some OEMs would like to see that drop to nearly 10 W.

Base station power supply current

Contact Us

For catalog requests, pricing, or partnerships, please visit:
<https://a-core.pl>