



## A-Core Container

# Government base station power supply supporting project



12.8V6Ah

Nominal voltage (V):12.8  
Nominal capacity (ah):6  
Rated energy (WH):76.8  
Maximum charging voltage (V):14.6  
Maximum charging current (a):6  
Floating charge voltage (V):13.6~13.8  
Maximum continuous discharge current (a):10  
Maximum peak discharge current @10 seconds (a):20  
Maximum load power (W):100  
Discharge cut-off voltage (V):10.8  
Charging temperature (°C):0~+50  
Discharge temperature (°C): -20~+60  
Working humidity: <95% R.H (non condensing)  
Number of cycles (25 °C, 0.5c, 100%dod): >2000  
Cell combination mode: 32700-4s1p  
Terminal specification: T2 (6.3mm)  
Protection grade: IP65  
Overall dimension (mm):90\*70\*107mm  
Reference weight (kg):0.7  
Certification: un38.3/msds



## Overview

---

These projects include a 1.73-megawatt photovoltaic system facility, a 12-megawatt grid-connected photovoltaic system with energy storage, enhancements to interior and exterior lighting in 118 buildings, upgrades to water fixtures in 64 buildings, and improvements to water and wastewater systems in three different locations.

## Government base station power supply supporting project

---

### Contact Us

---

For catalog requests, pricing, or partnerships, please visit:  
<https://a-core.pl>